# Product data sheet Characteristics

# 2510MCG3 MANUAL STARTER 600VAC

Product availability: Stock - Normally stocked in distribution facility

Price\*: 386.00 USD

Main	
Commercial Status	Commercialised
Product or component type	Manual Starter
Range of product	M
Product certifications	CSA UL listed
Auxiliary contact composition	Without
NEMA degree of protection	NEMA 1 painted sheet steel
Local signalling	No indicator
Motor power hp	10 hp 380575 V AC 3 phases 7.5 hp 200230 V AC 3 phases
[Ue] rated operational voltage	600 V AC
NEMA size	M-1
Poles description	3P
Control type	Pushbutton
Motor starter type	Non reversing
Electrical connection	Pressure wire clamp
Thermal overload type	Melting alloy
Number of thermal	3

## Ordering and shipping details

21103 - 2510,2511,2512 M,T	
CP1	
00785901792109	
1	
4.20	
Stock - Normally stocked in distribution facility	
Υ	
MX	
	CP1 00785901792109 1 4.20 Stock - Normally stocked in distribution facility Y

units required

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Will not be Compliant
REACh	Reference not containing SVHC above the threshold

#### Contractual warranty

Contractadi Warranty		
Period	18 months	