

Oatey®



Category 13

Air Admittance Valves (AAV)

Sensitivity to pressure changes, combined with its ability to consistently open and close, is what distinguishes the Oatey® Sure-Vent® AAV from all others. Superior engineering along with stringent quality standards ensure a lifetime of unmatched performance. Available in 6, 20, 160, and 500 DFU.

CATEGORY **13** AIR ADMITTANCE VALVES (AAV)

NEW Sure-Vent® AAV Wall Box (see pages 120)

When combined with 6 or 20 DFU air admittance valves, the **Oatey Sure-Vent AAV** wall boxes are a convenient solution for recessed installations. The high-impact polystyrene construction accommodates 1-1/2" to 2" adapters through the box opening while the textured grille faceplate conceals the AAV, providing a professional looking finish.

- **AAV mounts inside the wall box to the DWV system** via a 2" diameter molded-in drain port.
- **Box accommodates 6 or 20 DFU AAVs** with 1-1/2" or 2" adapters.
- **New smaller size** – 4-1/2" x 5-3/4" box for tight areas.
- **Adjustable faceplate** mounting with any wall finish provides a clean look.
- **Box and faceplate made from high-impact polystyrene.**
- **Available with PVC or ABS adapters.**
- **UPC listed.**



NEW!
From Oatey®



#39225 shown



Sure-Vent® Air Admittance Valve – 6 DFU Capacity

- Complies to ASSE Standard 1050 and 1051.
- For use as a secondary vent.
- One size approved to handle up to 2" vent pipe.
- Opens/closes as needed by building's plumbing system.

Product No.	Size	Description	Ctn. Qty.
39225	1.5"	6 DFU Sure-Vent AAV 1-1/2" Tubular adapter (white)	6
39226	1.5"	6 DFU Sure-Vent AAV 1-1/2" Tubular adapter (black)	6
39239	1.5"	6 DFU AAV Installation Kit 1-1/2" P-trap, 6" extension tube, PVC threaded adapter & deep box flange	6
39020	1.5"	6 DFU Sure-Vent AAV No adapter	50
39250	1.5" - 2"	6 DFU Sure-Vent AAV PVC Schedule 40, 90° adapter	6
39251	1.5" - 2"	6 DFU Sure-Vent AAV ABS Schedule 40, 90° adapter	6
39252	1.5" - 2"	6 DFU Sure-Vent AAV PVC Schedule 40, 90° adapter	50
39253	1.5" - 2"	6 DFU Sure-Vent AAV ABS Schedule 40, 90° adapter	50
39254	1.5" - 2"	6 DFU Sure-Vent AAV PVC Schedule 40 adapter	6
39256	1.5" - 2"	6 DFU Sure-Vent AAV ABS Schedule 40 adapter	6
39255	1.5" - 2"	6 DFU Sure-Vent PVC Schedule 40 Adapter	50



#39238 shown



Sure-Vent® Air Admittance Valve – 20 DFU Capacity

- Complies to ASSE Standard 1050 and 1051.
- For use as a secondary vent.
- One size approved to handle up to 3" vent pipe.
- Opens/closes as needed by building's plumbing system.

Product No.	Size	Description	Ctn. Qty.
39016	1.5" – 2"	20 DFU Sure-Vent AAV with 1 ½" x 2" PVC Schedule 40 Adapter	6
39018	1.5" – 2"	20 DFU Sure-Vent AAV with 1 ½" x 2" ABS Schedule 40 Adapter	6
39017	1.5" – 2"	20 DFU Sure-Vent AAV with 1 ½" x 2" PVC Schedule 40 Adapter	50
39019	1.5" – 2"	20 DFU Sure-Vent AAV with 1 ½" x 2" ABS Schedule 40 Adapter	50
39238	1.5" – 2"	20 DFU Sure-Vent AAV with mechanical adapter	12