

Industrial Gas Transformers

Ferromagnetic, Single Pole, One End Ground Models

These devices are designed for CONSTANT DUTY and provide the most reliable ignition source for commercial/industrial gas applications.

Absolute Maximum Ratings

Model #	1092	1112	1196	542
Input Supply Voltage (V)	120	240	240	120
Input Supply Frequency (Hz)	50/60	60	50	60
Primary Voltage - Amperes (VA)	150	150	150	265
Secondary Voltage (RMS)	6000	6000	6000	10000
Secondary Short Circuit Current (mA)	25/20	20	20	23
Storage Temperature (degrees C)	-40 to +80	-40 to +80	-40 to +80	-40 to +80
Operating Temperature (degrees C)	-30 to +40	-30 to +40	-30 to +40	-30 to +40
Operating Relative Humidity (%)	90	90	90	90
Loading Air Gap (inches)	1/16 - 1/8	1/16 - 1/8	1/16 - 1/8	1/16 - 1/8



www.allanson.com

USA | 99 Adams Blvd. | Farmingdale, New York | 11735
 Phone: 631-293-3880 | Fax 1-631-293-3470

CANADA | 33 Cranfield Road | Toronto, Ontario | M4B 3H2
 Phone: 416-755-1191 | Toll-Free 1-877-264-8444 | Fax 1-877-278-0907