

ELECTRICAL

START CAPACITORS 110V

ELECTROLYTIC CAPACITORS FOR MOTOR STARTING APPLICATIONS

FEATURES:

- Bakelite case
- Non-polarized aluminum electrolytic
- Quick connect terminals
- Capacitance Range:
21 to 1280 μ F
- Voltage Range:
110 to 330 VAC
- Operating Temperature:
-40°C to + 65°C
- Operating Frequency:
50 to 60 Hz
- Power Factor: 10% max.
(12% 30 μ F)
- Compact Size for Easy mounting
- Meets EIA RS-463 Type 2

VOLTAGE
RANGE IS 110
TO 330 VAC



START CAPACITORS 110V

PART NO	TYPE	MFD	VOLTAGE 110 V
72-86-110V	Plastic/Rnd.	72-86	110VAC
88-108-110V	Plastic/Rnd.	88-108	110VAC
108-130-110V	Plastic/Rnd.	108-130	110VAC
124-149-110V	Plastic/Rnd.	124-149	110VAC
130-156-110V	Plastic/Rnd.	130-156	110VAC
145-175-110V	Plastic/Rnd.	145-175	110VAC
161-193-110V	Plastic/Rnd.	161-193	110VAC
189-227-110V	Plastic/Rnd.	189-227	110VAC
216-259-110V	Plastic/Rnd.	216-259	110VAC
220-240-110V	Plastic/Rnd.	220-240	110VAC
233-280-110V	Plastic/Rnd.	233-280	110VAC
243-292-110V	Plastic/Rnd.	243-292	110VAC
270-324-110V	Plastic/Rnd.	270-324	110VAC
300-340-110V	Plastic/Rnd.	300-340	110VAC

PART NO	TYPE	MFD	VOLTAGE 110 V
324-389-110V	Plastic/Rnd.	324-389	110VAC
340-408-110V	Plastic/Rnd.	340-408	110VAC
378-490-110V	Plastic/Rnd.	378-490	110VAC
400-480-110V	Plastic/Rnd.	400-480	110VAC
430-516-110V	Plastic/Rnd.	430-516	110VAC
460-552-110V	Plastic/Rnd.	460-552	110VAC
540-648-110V	Plastic/Rnd.	540-648	110VAC
590-708-110V	Plastic/Rnd.	590-708	110VAC
708-850-110V	Plastic/Rnd.	708-850	110VAC
815-970-110V	Plastic/Rnd.	815-970	110VAC
829-995-110V	Plastic/Rnd.	829-995	110VAC
850-1020-110V	Plastic/Rnd.	850-1020	110VAC
1000-1200-110V	Plastic/Rnd.	1000-1200	110VAC



ENVIRONMENTALLY SMART