

## START CAPACITORS 220V AND 330V

### ELECTROLYTIC CAPACITORS FOR MOTOR STARTING APPLICATIONS

#### FEATURES:

- Bakelite case
- Non-polarized aluminum electrolytic
- Quick connect terminals
- Capacitance Range:  
21 to 1280  $\mu$ F
- Voltage Range: 110 to  
330 VAC
- Operating Temperature:  
-40°C to + 65°C
- Operating Frequency:  
50 to 60 Hz
- Power Factor: 10% max.  
(12% 30  $\mu$ F)
- Compact Size for  
Easy mounting
- Meets EIA RS-463 Type 2



### START CAPACITORS 220V AND 330V

| PART NO      | TYPE         | MFD      | VOLTAGE<br>220V |
|--------------|--------------|----------|-----------------|
| 21-25-220V   | Plastic/Rnd. | 21-25    | 220VAC          |
| 56-72-220V   | Plastic/Rnd. | 56-72    | 220VAC          |
| 72-86-220V   | Plastic/Rnd. | 72-86    | 220VAC          |
| 88-108-220V  | Plastic/Rnd. | 88-108   | 220VAC          |
| 108-130-220  | Plastic/Rnd. | 108-130  | 220VAC          |
| 124-149-220V | Plastic/Rnd. | 124-149  | 220VAC          |
| 130-156-220V | Plastic/Rnd. | 130-156  | 220VAC          |
| 145-175-220V | Plastic/Rnd. | 145-175  | 220VAC          |
| 189-227-220V | Plastic/Rnd. | 189-227  | 220VAC          |
| 216-259-220V | Plastic/Rnd. | 216-259  | 220VAC          |
| 233-280-220V | Plastic/Rnd. | 233-280A | 220VAC          |
| 243-292-220V | Plastic/Rnd. | 243-292  | 220VAC          |
| 270-324-220V | Plastic/Rnd. | 270-324  | 220VAC          |

| PART NO      | TYPE         | MFD     | VOLTAGE<br>330V |
|--------------|--------------|---------|-----------------|
| 21-25-330V   | Plastic/Rnd. | 21-25   | 330VAC          |
| 88-108-330V  | Plastic/Rnd. | 88-108  | 330VAC          |
| 108-130-330V | Plastic/Rnd. | 108-130 | 330VAC          |
| 124-149-330V | Plastic/Rnd. | 124-149 | 330VAC          |
| 130-156-330V | Plastic/Rnd. | 130-156 | 330VAC          |
| 145-175-330V | Plastic/Rnd. | 145-175 | 330VAC          |
| 189-227-330V | Plastic/Rnd. | 189-227 | 330VAC          |
| 216-259-330V | Plastic/Rnd. | 216-259 | 330VAC          |
| 270-324-330V | Plastic/Rnd. | 270-324 | 330VAC          |