

ELECTRICAL

CONTACTOR SERIES

SMART ELECTRIC CONTACTORS: These compact universal designs are commonly used in HVAC&R systems. Available in 1, 2 and 3 pole configurations, from 20A to 90A, offering a wide range of replacement options for Air Conditioning and Refrigeration applications.

FEATURES:

- 1, 2 and 3 Poles
- 24V, 120V, 240V Coil Voltage
- 20 to 90 Full Load Amps
- 25 to 100 Resistive Amps
- Lug Terminals
- Protective Cover



FIG. 1



FIG. 2

**DESIGNED FOR
AIR CONDITIONING,
REFRIGERATION
AND HEATING
EQUIPMENT**

SINGLE POLE CONTACTORS

CALUS

PART NO	FULL LOAD AMPS	RESISTIVE AMPS	LOCKED ROTOR AMPS@240	FIG	COIL VOLTAGE
SE6968M	40	50	240	1	24
SE2727M	30	40	180	1	240
SE2728M	30	40	180	1	120
SE2729M	30	40	180	1	24

2 POLE CONTACTORS

PART NO	FULL LOAD AMPS	RESISTIVE AMPS	LOCKED ROTOR AMPS@240	FIG	COIL VOLTAGE
SE2701M	20	25	120	2	120
SE2702M	20	25	120	2	240
SE2725M	25	30	150	2	120
SE2726M	25	30	150	2	24
SE2730M	30	40	180	2	24
SE2735M	30	40	180	2	120
SE2736M	30	40	180	2	240
SE2740M	40	50	240	2	24
SE2741M	40	50	240	2	120
SE2742M	40	50	240	2	240



ENVIRONMENTALLY SMART