

GENERAL PURPOSE FAN RELAYS

SMART ELECTRIC FAN RELAYS: Single pole single throw (SPST) and single pole double throw (SPDT) fan relays are ideal for switching solenoids, fan motors and other applications. These general purpose fan relays have universal mounting brackets. Available coil voltages are 24V, 110/120V, 208-240V.

SPST AND SPDT FAN RELAYS

REPLACE THE WR/ESSEX/RBM TYPE 84 (90-290 THRU 90-295) QUICK CONNECT

FEATURES:

- Universal mounting bracket
- Replace 90-290 thru 90-295
- Individually boxed
- Dimensions: 2.38" x 1.63" x 1.50"
- UL recognized component
- SPST and SPDT configurations
- 1/4" Quick-Connect Terminals
- 24V, 110/120V, 208/240V Coil Voltage



SPST AND SPDT FAN RELAYS

SPST NO	SPDT NO	COIL VOLTAGE
SE90290	SE90293	24
SE90291	SE90294	110/120
SE90292	SE90295	208/240

CONTACT RATING

FULL LOAD	LOCKED ROTOR	RESISTIVE	VOLTAGE
12	60	18	120
8	48	18	240
7	42	18	277

CROSS REFERENCE

SMART NO	WR/RBM NO	SMART NO	WR/RBM NO
SE90290	90-290Q	SE90293	90-293Q
SE90291	90-291Q	SE90294	90-294Q
SE90292	90-292Q	SE90295	90-295Q