

**Table 1**  
**CoreSense Communications Module Part Numbers**

| Voltage | OEM Part Number | Service Part Number |
|---------|-----------------|---------------------|
| 24      | 571-0065-04     | 971-0065-04         |
| 120/240 | 571-0064-05     | 971-0064-05         |

**Table 2**  
**CoreSense Communications Module Specifications**

| Module Part Number                        | 571-0065-04                  | 571-0064-05                  |
|-------------------------------------------|------------------------------|------------------------------|
| Module Voltage & Frequency                | 24 VAC, 50/60 HZ             | 120/240 VAC, 60HZ            |
|                                           |                              | 115/230 VAC, 50 HZ           |
| Allowable Voltage Range                   | 18 - 30 VAC                  | 85 - 265 VAC                 |
| T2/T1 Low Voltage Trip                    | 18 VAC                       | 85/170 VAC                   |
| T2/T1 Low Voltage Reset                   | 19 VAC                       | 95/185 VAC                   |
| Power Consumption                         | 5 VA                         | 5 VA                         |
| M1/M2 Contact Rating                      | 2.5A Max                     | 2.5A Max                     |
| Motor Temperature Trip Resistance         | > 4.5KΩ                      | > 4.5KΩ                      |
| Open Motor Thermistor Trip Resistance     | >220KΩ                       | >220KΩ                       |
| Shorted Motor Thermistor Trip Resistance  | <100Ω                        | <100Ω                        |
| Motor Temperature Reset Resistance        | < 2.75KΩ                     | < 2.75KΩ                     |
| Scroll Temperature Trip Resistance        | < 2.4KΩ                      | < 2.4KΩ                      |
| Open Scroll Thermistor Trip Resistance    | >370KΩ                       | >370KΩ                       |
| Shorted Scroll Thermistor Trip Resistance | <1KΩ                         | <1KΩ                         |
| Scroll Temperature Reset Resistance       | > 5.1KΩ                      | > 5.1KΩ                      |
| Reset Time After Trip                     | 30 minutes                   | 30 minutes                   |
| Operating Temperature                     | -40° to 150°F (-40° to 65°C) | -40° to 150°F (-40° to 65°C) |
| Storage Temperature                       | -60° to 175°F (-51° to 80°C) | -60° to 175°F (-51° to 80°C) |

**Table 3**  
**CoreSense Communications Accessory Parts**

| Part Description                | Part Number |
|---------------------------------|-------------|
| Scroll/Motor Thermistor Harness | 529-0102-00 |
| Phase Sensing Wires             | 529-0101-00 |