

CHARACTERISTICS		ELECTRICAL DATA		SCALE 1/2 TO 1
OPERATING FORCE — — — — —	3 LBS. MAX.	CONTACT ARRANGEMENT		DO NOT SCALE PRINT
FULL OVERTRAVEL FORCE — (A) —	4 LBS. MAX.	TWO CIRCUIT DOUBLE THROW		
RELEASE FORCE — — — — —	1/4 LB. MIN.	DOUBLE BREAK		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: ONE PLACE (.0) ±.030 TWO PLACE (.00) ±.015 THREE PLACE (.000) ±.001 ANGLES ± WEIGHT
PRETRAVEL — — — — — (3) —	15° MAX.	10A-120,240, OR 480 VAC, 1/2 H.P.-120 VAC 1 H.P.-240 VAC, 0.8 A-115 VDC, 0.4 A-230 VDC PILOT DUTY. 720 VA HEAVY DUTY 600 VAC MAX 		
DIFFERENTIAL TRAVEL — — — — — (4) —	7° MAX.			
OVERTRAVEL — — — — — (5) —	60° MIN.			
SWITCH-BASIC REPLACEMENT — — — — —	1 MN1			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell:](#)

[151ML1-E1](#)