

ZR57K3E-TF5

HCFC, R-22, 60Hz, 3- Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65 / 115	65 / 85
Capacity (Btu/hr)	58500	68500
Power (Watts):	4980	3430
Current (Amps):	14.50	11.10
EER (Btu/Wh):	11.70	20.00
Mass Flow (lbs/hr):	860	880
Sound Power (dBA):	74 Avg	79 Max
Vibration (mils(peak- Record Date:	2.0 Avg 2014-03-06	3.0 Max

Mechanical

Number of Cylinders:0	Displ(in^3/Rev):	4.71	
Bore Size(in):	0.00	Displ(ft^3/hr):	572.40
Stroke(in):	0.00		
Overall Length (in):	9.69	Mounting Length (in):	7.50
Overall Width (in):	9.69	Mounting Width (in):	7.50
Overall Height (in):	17.24	Mounting Height (in):	17.99 *
Suction Size (in):	7/8 Stub		
Discharge Size (in):	1/2 Stub		
Oil Recharge (oz):	62		
Initial Oil Charge (oz):	66		
Net Weight (lbs):	85		
Internal Free Volume (in^3):	257.0		
Horse Power:	4.75		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	123.0	MCC (Amps):	27.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:		UL File Date:	26-Jul-1993
LRA Low*:		Max Operating Current:	18.0		
RLA(=MCC/1.4;use for contactor selection):		19.3			
RLA(=MCC/1.56;use for breaker & wire size		17.3			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-407C HFC	50	3	200/220	Air Conditioning
R-22 HCFC	50	3	200/220	Air Conditioning
R-407C HFC	60	3	200/230	Air Conditioning

ZR57K3E-TF5

HCFC, R-22, 60Hz, 3- Phase, 200/230 V
Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Service Parts

<u>Reference</u>	<u>Component</u>	<u>Quantity</u>	<u>Description</u>	<u>Comment</u>
99	527-0116-00	1	SPACER-MOUNTING ASSM	
99	918-0043-00	1	HEATER-CRANKCASE	240V 70W WRAP AROUND
99	918-0043-01	1	HEATER-CRANKCASE	480V 70W WRAP AROUND

ZR57K3E-TF5

HCFC, R-22, 60Hz, 3- Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Accessories

<u>PartNumber</u>	<u>Description</u>
018-0095-00	Crankcase Heater, 240V, 70W, 21" Lead Length
018-0095-01	Crankcase Heater, 480V, 70W, 21" Lead Length
018-0095-02	Crankcase Heater, 575V, 70W, 21" Lead Length
018-0095-03	Crankcase Heater, 240V, 70W, 32" Lead Length
018-0095-04	Crankcase Heater, 240V, 70W, 48" Lead Length
018-0095-05	Crankcase Heater, 480V, 70W, 48" Lead Length
018-0095-06	Crankcase Heater, 575V, 70W, 48" Lead Length
018-0095-07	Crankcase Heater, 120V, 70W, 48" Lead Length
018-0095-08	Crankcase Heater, 400V, 70W, 48" Lead Length
018-0095-09	Crankcase Heater, 277V, 70W, 21" Lead Length
018-0095-00	Crankcase Heater, 240V, 70W, 21" Lead Length
018-0095-01	Crankcase Heater, 480V, 70W, 21" Lead Length
018-0095-02	Crankcase Heater, 575V, 70W, 21" Lead Length
018-0095-03	Crankcase Heater, 240V, 70W, 32" Lead Length
018-0095-04	Crankcase Heater, 240V, 70W, 48" Lead Length
018-0095-05	Crankcase Heater, 480V, 70W, 48" Lead Length
018-0095-06	Crankcase Heater, 575V, 70W, 48" Lead Length
018-0095-07	Crankcase Heater, 120V, 70W, 48" Lead Length
018-0095-08	Crankcase Heater, 400V, 70W, 48" Lead Length
018-0095-09	Crankcase Heater, 277V, 70W, 21" Lead Length
085-0160-00	3 Phase Voltage Monitor. For use with all Copeland 3 Phase Compressors. Consult model family nomenclature for electrical definition in the model number.
527-0116-00	Kit: Spacer Mounting, 30-35 Durometer, 1.45" OD, 0.44" ID, 0.75" Height
918-0043-00	Kit: Crankcase Heater, 240V, 70W, Wrap Around 48" Leads
918-0043-01	Kit: Crankcase Heater, 480V, 70W, Wrap Around 48" Leads
918-0043-02	Kit: Crankcase Heater, 575V, 70W, Wrap Around 48" Leads
918-0043-07	Kit: Crankcase Heater, 120V, 70W, Wrap Around 48" Leads
998-E022-01	Polyol Ester Oil. Approved for use with specific Copeland Hermetic & Semi Hermetic models. Consult specific model family nomenclatures for oil identifier in the model number.

Scott Kohler

Page 1 of 1

05/27/2014

Common U.S. OEM Bill Of Materials

	Suction Connection	Suction Size	Discharge Connection	Discharge Size	Electrical Connection	Mounting Assembly	Sight Glass	Crankcase Heater	Schraeder Valve	Tandem Ready	Module Voltage
230	Stub	7/8"	Stub	1/2"	SCREW 1/2 Conduit	-	-	-	-	-	-
250	Stub	7/8"	Stub	1/2"	SCREW 1/2 Conduit	-	-	-	-	-	-
260	Rotalock	1 1/4"	Rotalock	1"	SCREW 1/2 Conduit	-	-	-	-	-	-
265	Rotalock	1 1/4"	Rotalock	1"	SCREW 1/2 Conduit	-	-	-	-	-	-

Common U.S. Service Bill Of Materials

	Suction Connection	Suction Size	Discharge Connection	Discharge Size	Electrical Connection	Mounting Assembly	Sight Glass	Crankcase Heater	Schraeder Valve	Tandem Ready	Module Voltage
930	Stub	7/8"	Stub	1/2"	SCREW 1/2 Conduit	Yes	-	-	-	-	-
950	Stub	7/8"	Stub	1/2"	SCREW 1/2 Conduit	Yes	-	-	-	-	-
965	Rotalock	1 1/4"	Rotalock	1"	SCREW 1/2 Conduit	Yes	-	-	-	-	-

*** Note: For all other Bill Of Material descriptions (Including International and Customer Specific Bills of Materials) contact your sales representative or the Application Engineering Department.**