

Definite Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Hostile Duty, Inverter Duty 20:1 (3-60 Hertz) Speed Range Variable Torque 5:1 (12-60 Hertz) Speed Range Constant Torque



CTI

APPLICATIONS:

For use on pumps, fans, blowers or other variable torque applications. Constant torque applications requiring 5:1 or less speed range and applications requiring a drive bypass.

FEATURES:

- INVERTER GRADE® Insulation System (Meets NEMA® MG-1 Part 31)
- Class F Thermostats (One Per Phase)
- Cast Iron Frame (140: Rolled Steel), Cast Iron End Brackets
- Corrosion Resistant Mill & Chemical Duty Paint
- Stainless Steel Nameplate & Zinc Plated Hardware
- Shaft Slinger On Pulley End For IP54 Protection
- 40°C Ambient, NEMA® Design B Performance On 60 Hertz Sine Wave Power
- 1.15 Service Factor On Sine Wave / 1.0 Service Factor On PWM
- Special Balance
- Regreasable Bearings 250 Frame & Up
- Double Shielded Bearings 140-360, Open On 400-440
- Double Dip & Bake With Extra Bracing
- Premium Efficient Design, F1 Assembly Position
- Class F Insulation, 1.15 Service Factor On Sine Wave / 1.0 Service Factor On PWM
- Constant Horsepower To 90 Hertz
- Conversion Kits: All Cast Iron Upgrade, C&D Flanges, Canopy Kits (except 320-360)
- C-Face Footed 1-5 HP

HP	RPM (Max Speed)	Voltage	Frame	Catalog Number	List	Discount Symbol	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
1	1800(3600)	230/460	143TC	H1V2BC	\$573	DS-VST	12.6	67	85.5	2.9/1.5	
	1200(2400)	230/460	145TC	H1V3BC	\$779	DS-VST	12.6	72	81.5	3.7/1.9	
1 1/2	3600(7200)	230/460	143TC	H32V1BC	\$660	DS-VST	12.6	65	84.0	3.9/1.9	
	1800(3600)	230/460	145TC	H32V2BC	\$635	DS-VST	12.6	72	85.5	4.4/2.2	
	1200(2400)	230/460	182TC	H32V3BC	\$864	DS-VST	16.8	100	86.5	5/2.5	
2	3600(7200)	230/460	145TC	H2V1BC	\$784	DS-VST	12.6	72	86.5	4.9/2.4	
	1800(3600)	230/460	145TC	H2V2BC	\$696	DS-VST	12.6	82	85.5	5.5/2.8	
	1200(2400)	230/460	184TC	H2V3BC	\$961	DS-VST	15.6	110	87.5	6/3	
3	3600(7200)	230/460	182TC	H3V1BC	\$882	DS-VST	16.0	100	87.5	7.6/3.8	
	1800(3600)	230/460	182TC	H3V2BC	\$780	DS-VST	16.8	100	89.5	7.8/3.9	
	1200(2400)	230/460	213TC	H3V3BC	\$1,191	DS-VST	19.1	160	90.2	8.7/4.4	
5	3600(7200)	230/460	184TC	H5V1BC	\$1,106	DS-VST	16.8	110	88.5	12.2/6.1	
	1800(3600)	230/460	184TC	H5V2BC	\$906	DS-VST	16.8	110	89.5	12.8/6.4	
	1200(2400)	230/460	215TC	H5V3BC	\$1,705	DS-VST	20.6	175	90.2	14/7	
7 1/2	3600(7200)	230/460	213T	H7V1B	\$1,371	DS-VST	17.6	160	91.0	17.8/8.9	
	1800(3600)	230/460	213T	H7V2B	\$1,240	DS-VST	19.2	167	91.0	18.4/9.2	
	1200(2400)	230/460	254T	H7V3B	\$2,276	DS-VST	25.3	300	91.0	18.6/9.3	
10	3600(7200)	230/460	215T	H10V1B	\$1,607	DS-VST	19.2	175	91.0	23.2/11.6	
	1800(3600)	230/460	215T	H10V2B	\$1,497	DS-VST	19.1	175	91.7	23.8/11.9	
	1200(2400)	230/460	256T	H10V3B	\$2,749	DS-VST	25.5	352	91.7	24.5/12.3	
15	3600(7200)	230/460	254T	H15V1B	\$2,299	DS-VST	25.3	300	90.2	35/17.7	
	1800(3600)	230/460	254T	H15V2B	\$2,068	DS-VST	25.3	300	92.4	37/18.4	
	1200(2400)	230/460	284T	H15V3B	\$3,831	DS-VST	35.7	380	91.7	37/18.7	
20	3600(7200)	230/460	256T	H20V1B	\$2,846	DS-VST	25.5	362	90.2	47/23.4	
	1800(3600)	230/460	256T	H20V2B	\$2,548	DS-VST	25.5	372	93.0	47/23.7	
	1200(2400)	230/460	286T	H20V3B	\$4,640	DS-VST	27.0	410	91.7	49/24.5	
25	3600(7200)	230/460	284TS	H25V1BS	\$3,491	DS-VST	25.6	380	91.7	59/29.5	
	1800(3600)	230/460	284T	H25V2B	\$3,058	DS-VST	27.0	380	93.0	59/29.4	
	1200(2400)	230/460	324T	H25V3B	\$5,521	DS-VST	30.6	600	93.0	62/31	
30	3600(5400)	230/460	286TS	H30V1BS	\$4,094	DS-VST	25.6	400	91.7	69/35	
	1800(2700)	230/460	286T	H30V2B	\$3,566	DS-VST	27.0	440	93.6	69/34	
	1200(2400)	230	326T	H30V3B	\$6,515	DS-VST	30.6	675	93.0	74	

† All marks shown within this document are properties of their respective owners.



GEN. PURPOSE UNIMOUNT
GENERAL PURPOSE STEEL EDGE™
GENERAL PURPOSE HOSTILE DUTY
GENERAL PURPOSE CORRO-DUTY™
GENERAL PURPOSE 841 PLUS™
GENERAL PURPOSE OPEN DRIPPROOF
GENERAL PURPOSE HAZARDOUS LOCATION
GENERAL PURPOSE AUTOMOTIVE DUTY
COOLING TOWER DUTY
HAZARDOUS LOCATION
C-FACE MOTORS
VARIABLE SPEED MOTORS AND DRIVES

GEN. PURPOSE
UNIMOUNT

Definite Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Hostile Duty, Inverter Duty 20:1 (3-60 Hertz) Speed Range Variable Torque 5:1 (12-60 Hertz) Speed Range Constant Torque

GENERAL PURPOSE
"STEEL EDGE"*(continued)*GENERAL PURPOSE
HOSTILE DUTYGENERAL PURPOSE
CORRO-DUTYGENERAL PURPOSE
841 PLUS*GENERAL PURPOSE
OPEN DRIPPROOFGENERAL PURPOSE
HAZARDOUS
LOCATIONGENERAL PURPOSE
AUTOMOTIVE DUTYCOOLING TOWER
DUTYHAZARDOUS
LOCATIONC-FACE
MOTORSVARIABLE
SPEED MOTORS
AND DRIVES

HP	RPM (Max Speed)	Voltage	Frame	Catalog Number	List	Discount Symbol	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Eff.	Full Load Amps	Notes
40	3600(5400)	230/460	324TS	H40V1BS	\$5,290	DS-VST	29.1	560	92.4	91/46	
	1800(2700)	230/460	324T	H40V2B	\$4,656	DS-VST	30.6	600	94.1	92/46	
	1200(2400)	230/460	364T	H40V3B	\$8,775	DS-VST	32.6	906	94.1	93/46	
50	3600(5400)	230/460	326TS	H50V1BS	\$6,807	DS-VST	29.1	600	93.0	112/56	
	1800(2700)	230/460	326T	H50V2B	\$5,717	DS-VST	30.6	710	94.5	113/56	
	1200(2400)	230/460	365T	H50V3B	\$10,109	DS-VST	32.6	900	94.1	116/58	
60	3600(5400)	230/460	364TS	H60V1BS	\$9,086	DS-VST	30.4	790	93.6	136/68	
	1800(2700)	230/460	364T	H60V2B	\$8,312	DS-VST	32.6	825	95.0	138/69	
	1200(2400)	230/460	404T	H60V3B	\$11,909	DS-VST	37.6	1160	94.5	140/70	
75	3600(4500)	230/460	365TS	H75V1BS	\$11,411	DS-VST	30.4	830	93.6	167/83	
	1800(3600)	230/460	365T	H75V2B	\$10,572	DS-VST	32.6	225	95.0	168/84	
	1200(2400)	230/460	405T	H75V3B	\$14,042	DS-VST	37.6	1300	94.5	175/87	
100	3600(4500)	230/460	405TS	H100V1BS	\$15,290	DS-VST	34.6	1200	94.5	218/109	
	1800(3600)	230	405T	H100V2B	\$13,028	DS-VST	37.6	1250	95.4	225	
	1200(2400)	460	444T	H100V3C	\$19,226	DS-VST	45.8	1660	95.0	122	
125	3600(4500)	460	444TS	H125V1CS	\$19,027	DS-VST	41.66	1550	95.8	142	
	1800(3600)	460	444T	H125V2C	\$16,217	DS-VST	45.8	1675	95.4	146	
	1200(2400)	460	445T	H125V3C	\$21,991	DS-VST	45.8	1750	95.4	151	
150	3600(4500)	460	445TS	H150V1CS	\$23,415	DS-VST	41.66	1625	95.8	171	
	1800(3600)	460	445T	H150V2C	\$19,249	DS-VST	45.4	1800	95.8	171	
	1200(2400)	460	445T	H150V3C	\$25,259	DS-VST	45.4	1750	95.4	153	
200	3600(4500)	460	447TS	H200V1CS	\$29,591	DS-VST	45.16	2100	96.2	217	
	1800(3600)	460	447T	H200V2C	\$23,452	DS-VST	48.9	2143	95.8	226	

† All marks shown within this document are properties of their respective owners.

