

1. Product and Company Identification



Product identifier	Spray-N-Bond (4369-75)			
Other means of identification	Not available Adhesive. None known.			
Recommended use				
Recommended restrictions				
Manufacturer information	Nu-Calgon 2611 Schuetz Road St. Louis, MO 63043 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTI	REC)		
Supplier	See above.			
	2. Hazards Identification	n		
Physical hazards	Flammable aerosols	Category 1		
	Gases under pressure	Liquefied gas		
Health hazards	Skin corrosion/irritation	Category 2		
	Serious eye damage/eye irritation	Category 2		
	Sensitization, skin	Category 1		
	Reproductive toxicity	Category 2		
	Specific target organ toxicity, single exposure	Category 3 narcotic effects		
	Aspiration hazard	Category 1		
Environmental hazards	Not classified.			
WHMIS 2015 defined hazards	Not classified			
Label elements				
Signal word	Danger			
Hazard statement	swallowed and enters airways. Causes skin in	nder pressure; may explode if heated. May be fatal if ritation. May cause an allergic skin reaction. Causes or dizziness. Suspected of damaging fertility or the		
Precautionary statement				
Prevention	Do not spray on an open flame or other ignitio Wash thoroughly after handling. Wear protecti protection. Contaminated work clothing should	ben flames and other ignition sources. No smoking. n source. Do not pierce or burn, even after use. ve gloves/protective clothing/eye protection/face d not be allowed out of the workplace. Use only becial instructions before use. Do not handle until all stood. Avoid breathing gas.		
Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.			
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a well-ventilated place.			
Disposal	Dispose of contents/container in accordance w	vith local/regional/national/international regulations.		
	N1 1			

WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)

None known

Supplemental information

None known.

None.

3. Composition/Information on Ingredients

#### Mixture

hemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	20-30
Propane		74-98-6	20-30
Butane		106-97-8	10-30
Naphtha (petroleum), hydrotreated light		64742-49-0	10-30
1,3-butadiene, 2-methyl-, Homopolymer, Maleated		841251-34-1	1-5
Methyl acetate		79-20-9	1-5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

**Composition comments** 

	4. First Aid Measures		
Inhalation	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.		
Skin contact	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label).		
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.		
Ingestion	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.		
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.		
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. Avoid contact with eyes and skin. Keep out of reach of children.		
5. Fire Fighting Measures			
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide.		
Uncuitable extinguishing	Not available		

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide.
Unsuitable extinguishing media	Not available.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Not available.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

	6. Accidental Release Measures			
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.			
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.			
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.			
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.			
	7. Handling and Storage			
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not smoke while using or until sprayed surface is thoroughly dry. Pressurized container: Do not piero or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a nake flame or any other incandescent material. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Use only in well-ventilated areas. Avoid prolonged exposure. Wear appropriate persona protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.			
Conditions for safe storage, including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture, incinerate or crush. Store in a well-ventilated place. Cylinders should b stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Keep out of reach of children.			

# 8. Exposure Controls/Personal Protection

#### **Occupational exposure limits**

Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	1800 mg/m3 750 ppm	
	TWA	1200 mg/m3 500 ppm	
Benzene, ethenyl- (CAS 100-42-5)	STEL	170 mg/m3	
		40 ppm	
	TWA	85 mg/m3 20 ppm	
Butane (CAS 106-97-8)	TWA	1000 ppm	
Methyl acetate (CAS 79-20-9)	STEL	757 mg/m3	
,		250 ppm	
	TWA	606 mg/m3 200 ppm	
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m3	
		400 ppm	
Propane (CAS 74-98-6)	TWA	1000 ppm	

Safety Regulation 296/97, as amo	ended)	-	
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Benzene, ethenyl- (CAS 100-42-5)	STEL	75 ppm	
	TWA	50 ppm	
Butane (CAS 106-97-8)	STEL	750 ppm	
	TWA	600 ppm	
Methyl acetate (CAS 79-20-9)	STEL	250 ppm	
	TWA	200 ppm	
Propane (CAS 74-98-6)	TWA	1000 ppm	

# Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

#### Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Benzene, ethenyl- (CAS 100-42-5)	STEL	40 ppm	
	TWA	20 ppm	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Methyl acetate (CAS 79-20-9)	STEL	250 ppm	
	TWA	200 ppm	

#### Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Benzene, ethenyl- (CAS 100-42-5)	STEL	100 ppm	
	TWA	35 ppm	
Butane (CAS 106-97-8)	TWA	800 ppm	
Methyl acetate (CAS 79-20-9)	STEL	250 ppm	
	TWA	200 ppm	
Propane (CAS 74-98-6)	TWA	1000 ppm	

## Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	2380 mg/m3 1000 ppm
	TWA	1190 mg/m3 500 ppm
Benzene, ethenyl- (CAS 100-42-5)	STEL	426 mg/m3
		100 ppm
	TWA	213 mg/m3 50 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Methyl acetate (CAS 79-20-9)	STEL	757 mg/m3
,		250 ppm
	TWA	606 mg/m3 200 ppm

Canada. Quebec OELs. (Ministry of Labo Components	or - Regulation Respecting the Qual Type	ity of the Work Environment) Value
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m3
,		400 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm
US. OSHA Table Z-1 Limits for Air Conta Components	uminants (29 CFR 1910.1000) Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3
		1000 ppm
Methyl acetate (CAS 79-20-9)	PEL	610 mg/m3
13-20-3)		200 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m3
01112 10 0)		100 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
US. OSHA Table Z-2 (29 CFR 1910.1000)		Value
Components	Туре	Value
Benzene, ethenyl- (CAS 100-42-5)	Ceiling	200 ppm
	TWA	100 ppm
US. ACGIH Threshold Limit Values	_	
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Benzene, ethenyl- (CAS 100-42-5)	STEL	40 ppm
	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Methyl acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm
US. NIOSH: Pocket Guide to Chemical H		
Components	Туре	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
Benzene, ethenyl- (CAS 100-42-5)	STEL	425 mg/m3
		100 ppm
	TWA	215 mg/m3 50 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Methyl acetate (CAS 79-20-9)	STEL	760 mg/m3
		250 ppm
	TWA	610 mg/m3 200 ppm
	TWA	400 mg/m3
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		J.
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		100 ppm

## **Biological limit values**

## **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	25 mg/L	Acetone	Urine	*	
Benzene, ethenyl- (CAS 100-42-5)	40 µg/l	Styrene	Urine	*	
,	400 mg/g	Mandelic acid plus phenylglyoxylic acid	Creatinine in urine	*	

\* - For sampling details, please see the source document.

#### Exposure guidelines

Expediate guidelines		
Canada - Alberta OELs: Skin	designation	
Benzene (CAS 71-43-2)		Can be absorbed through the skin.
Methanol (CAS 67-56-1)		Can be absorbed through the skin.
Naphthalene (CAS 91-20-	.3)	Can be absorbed through the skin.
Phenol (CAS 108-95-2)	-,	Can be absorbed through the skin.
Toluene (CAS 108-88-3)		Can be absorbed through the skin.
Canada - British Columbia O	ELs: Skin designation	
	g	Can be absorbed through the skin.
Benzene (CAS 71-43-2) Methanol (CAS 67-56-1)		Can be absorbed through the skin.
( ) /	2)	Can be absorbed through the skin.
Naphthalene (CAS 91-20- Phenol (CAS 108-95-2)	5)	Can be absorbed through the skin.
Canada - Manitoba OELs: Sk	in decignation	Can be absorbed through the skin.
Benzene (CAS 71-43-2)		Can be absorbed through the skin.
Methanol (CAS 67-56-1)		Can be absorbed through the skin.
Naphthalene (CAS 91-20-	3)	Can be absorbed through the skin.
Phenol (CAS 108-95-2)		Can be absorbed through the skin.
Canada - Ontario OELs: Skin	designation	
Benzene (CAS 71-43-2)		Can be absorbed through the skin.
Methanol (CAS 67-56-1)		Can be absorbed through the skin.
Naphthalene (CAS 91-20-	·3)	Can be absorbed through the skin.
Phenol (CAS 108-95-2)		Can be absorbed through the skin.
Canada - Quebec OELs: Skin	1 designation	
Benzene, ethenyl- (CAS 1	00-42-5)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)		Can be absorbed through the skin.
Phenol (CAS 108-95-2)		Can be absorbed through the skin.
Toluene (CAS 108-88-3)		Can be absorbed through the skin.
Canada - Saskatchewan OEL	s: Skin designation	5
Methanol (CAS 67-56-1)	5	Can be absorbed through the skin.
Naphthalene (CAS 91-20-	.3)	Can be absorbed through the skin.
Phenol (CAS 108-95-2)	0)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)		Can be absorbed through the skin.
US ACGIH Threshold Limit V	alues: Skin designation	
		Can be abaarhad through the alvin
Benzene (CAS 71-43-2)		Can be absorbed through the skin.
Methanol (CAS 67-56-1)	2)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-	3)	Can be absorbed through the skin.
Phenol (CAS 108-95-2) US. NIOSH: Pocket Guide to	Chamical Herende	Can be absorbed through the skin.
Benzene, (1-methylethyl)-	(CAS 98-82-8)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)		Can be absorbed through the skin.
Phenol (CAS 108-95-2)		Can be absorbed through the skin.
US. OSHA Table Z-1 Limits for		-
Benzene, (1-methylethyl)-	(CAS 98-82-8)	Can be absorbed through the skin.
Phenol (CAS 108-95-2)		Can be absorbed through the skin.
Appropriate engineering controls	should be matched to condi or other engineering control	pically 10 air changes per hour) should be used. Ventilation rates tions. If applicable, use process enclosures, local exhaust ventilation, s to maintain airborne levels below recommended exposure limits. If en established, maintain airborne levels to an acceptable level.
Individual protection measures, s	•	· · ·
Eye/face protection	Wear safety glasses with sid	
Skin protection	, , ,	

Hand protection

Impervious gloves. Confirm with reputable supplier first.

Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. As required by employer code.
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not applicable.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink.

	5. Filysical and Chemical Flopences
Appearance	Clear
Physical state	Gas.
Form	Spray
Color	Yellow
Odor	Solvent
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	Not available.
Specific gravity	0.84
Partition coefficient (n-octanol/water)	Not available.
Flash point	-156.0 °F (-104.4 °C) (Propellant)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	135 - 155 psi @ 130°F 65 - 85 psi @ 70°F
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	7 - 200 cps
Other information	
Explosive properties	Not explosive.
Flame projection	32 in
Flammability (flash back)	2 Yes
Heat of combustion	> 30 kJ/g
Oxidizing properties	Not oxidizing.
	10. Stability and Reactivity
Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

Material is stable under normal conditions.

**Chemical stability** 

# 11. Toxicological Information

Routes of exposure	Eye, Skin contact, Inhalation, Inges	tion.		
Information on likely routes of	exposure			
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May cause stomach distress, nausea or vomiting.			
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.			
Skin contact	Causes skin irritation. May cause a	Causes skin irritation. May cause an allergic skin reaction.		
Eye contact	Causes serious eye irritation.			
Symptoms related to the ohysical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.			
nformation on toxicological ef	ffects			
Acute toxicity	May be fatal if swallowed and enter reaction.	s airways. Narcotic effects. May cause an allergic skin		
Components	Species	Test Results		
1,3-butadiene, 2-methyl-, Homop	polymer, Maleated (CAS 841251-34-1)			
Acute				
Dermal LD50	Not available			
Inhalation LC50	Not available			
Oral LD50	Not available			
Acetone (CAS 67-64-1)				
Acute				
Dermal				
LD50	Rabbit	15800 mg/kg		
		20 ml/kg		
Inhalation LC50	Mouro	11000 mg/m2/1H		
LC30	Mouse	44000 mg/m3/4H		
	Rat	76 mg/L, 4 Hours		
		50.1 mg/L, 8 Hours		
		39 mg/l/4h		
Oral LD50	Human	2857 mg/kg		
EDS0	Mouse	3000 mg/kg		
		0.0		
	Rabbit	5340 mg/kg		
	Rat	5800 mg/kg		
Butane (CAS 106-97-8)				
Acute Dermal				
LD50	Not available			
Inhalation				
LC50	Mouse	539600 ppm, 120 Minutes, ECHA		
		520400 ppm, 120 Minutes, ECHA		
		1237 mg/L, 120 Minutes		
		680 mg/L, 2 Hours, HSDB		
		57 %, 120 Minutes, ECHA		

Components	Species	<b>Test Results</b> 52 %, 120 Minutes
	Rat	> 800000 ppm, 10 Minutes, ECHA 1442738 mg/m3, 10 Minutes, ECHA
		1354944 mg/m3, 10 Minutes, ECHA
		570000 ppm, 10 Minutes, ECHA
		276000 ppm, 4 Hours, CCOHS
		1443 mg/L, 10 Minutes, ECHA
Oral		1355 mg/L, 10 Minutes
LD50	Not available	
Methyl acetate (CAS 79-20-9)		
Acute		
Dermal LD50	Dobbit	5 5000 mg///g
Inhalation	Rabbit	> 5000 mg/kg
LC50	Rat	> 16000 ppm
Oral		
LD50	Rabbit	3705 mg/kg
		3.7 g/kg
	Rat	> 5000 mg/kg
Naphtha (petroleum), hydrotre	ated light (CAS 64742-49-0)	
Acute Dermal		
LD50	Rabbit	3160 mg/kg
Inhalation		
LC50	Rat	61 mg/L, 4 Hours
		20 ppm
		20 mg/l/4h
Oral	Rat	> 25 ml/kg
LD50	Nal	•
Propane (CAS 74-98-6)		5000 mg/kg
Acute		
Dermal		
LD50	Not available	
Inhalation	M	
LC50	Mouse	539600 ppm, 120 Minutes, ECHA
		520400 ppm, 120 Minutes, ECHA
		1237 mg/L, 120 Minutes
		57 %, 120 Minutes, ECHA 52 %, 120 Minutes
	Rat	> 12000000 ppm, 4 hours
	Nal	> 800000 ppm, 10 Minutes, ECHA
		> 1464 mg/L, 15 Minutes, HSDB
		1442738 mg/m3, 10 Minutes, ECHA
		1354944 mg/m3, 10 Minutes, ECHA
		570000 ppm, 10 Minutes, ECHA
		1355 mg/L, 10 Minutes
		1000 mg/L, 10 minutes
Oral		

Skin corrosion/irritation	Causes skin irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Canada - Alberta OELs: Irrita		
Acetaldehyde (CAS 75-07 Phenol, 2,6-bis(1,1-dimetl 128-37-0)		Irritant Irritant
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin rea	ction.
Mutagenicity	No data available to indicate p mutagenic or genotoxic.	roduct or any components present at greater than 0.1% are
Carcinogenicity	See below.	
ACGIH Carcinogens		
Acetaldehyde (CAS 75-07	7-0)	A2 Suspected human carcinogen.
Benzene (CAS 71-43-2)	× 44 - 4\	A1 Confirmed human carcinogen.
Benzene, ethyl- (CAS 100	)-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Naphthalene (CAS 91-20-	3)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Canada - Alberta OELs: Caro	cinogen category	
Benzene (CAS 71-43-2) Canada - Manitoba OELs: ca	rcinogonicity	Confirmed human carcinogen.
ACETALDEHYDE (CAS 7	• •	Suspected human carcinogen.
ACETONE (CAS 67-64-1)		Not classifiable as a human carcinogen.
BENZENE (CAS 71-43-2)		Confirmed human carcinogen.
FRACTION AND VAPOR	TOLUENE (BHT), INHALABLE (CAS 128-37-0)	Not classifiable as a human carcinogen.
ETHYL BENZENE (CAS		Confirmed animal carcinogen with unknown relevance to humans.
NAPHTHALENE (CAS 91	,	Confirmed animal carcinogen with unknown relevance to humans.
PHENOL (CAS 108-95-2) STYRENE, MONOMER (		Not classifiable as a human carcinogen. Not classifiable as a human carcinogen.
TOLUENE (CAS 108-88-3		Not classifiable as a human carcinogen.
Canada - Quebec OELs: Car		-
Acetaldehyde (CAS 75-07	7-0)	Detected carcinogenic effect in animals.
Benzene (CAS 71-43-2) Benzene, ethenyl- (CAS 1	00-42-5)	Detected carcinogenic effect in humans. Detected carcinogenic effect in animals.
IARC Monographs. Overall E		
Acetaldehyde (CAS 75-07	7-0)	Volume 36, Supplement 7, Volume 71 - 2B Possibly carcinogenic to humans.
Benzene (CAS 71-43-2)		Volume 29, Supplement 7, Volume 100F 1 Carcinogenic to humans.
Benzene, (1-methylethyl)- (CAS 98-82-8)		Volume 101 - 2B Possibly carcinogenic to humans.
Benzene, ethenyl- (CAS 100-42-5) Benzene, ethyl- (CAS 100-41-4)		Volume 60, Volume 82 - 2B Possibly carcinogenic to humans. Volume 77 - 2B Possibly carcinogenic to humans.
Naphthalene (CAS 91-20-3)		Volume 82 - 2B Possibly carcinogenic to humans.
Phenol (CAS 108-95-2)		Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (CAS 128-37-0)		humans. Volume 40, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.
Toluene (CAS 108-88-3)		Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.
US - California Proposition 6	5 - CRT: Listed date/Carcinog	
Acetaldehyde (CAS 75-07 Benzene (CAS 71-43-2)	7-0)	

Benzene, (1-methylethyl		)		
Benzene, ethenyl- (CAS				
Benzene, ethyl- (CAS 10 Naphthalene (CAS 91-2				
US NTP Report on Carcino		ed carcinogen		
Acetaldehyde (CAS 75-0		-	d to be a Human Carcinogen.	
Benzene, (1-methylethyl	I)- (CAS 98-82-8		d to be a Human Carcinogen.	
Benzene, ethenyl- (CAS			d to be a Human Carcinogen.	
Naphthalene (CAS 91-2 US NTP Report on Carcino			d to be a Human Carcinogen.	
Benzene (CAS 71-43-2)	•	Known To Be Human (	Carcinogen	
( )		ces (29 CFR 1910.1001-1050)	bareinogen.	
Benzene (CAS 71-43-2)		Cancer		
Reproductive toxicity		damaging fertility or the unborn child.		
Teratogenicity	Not available			
Specific target organ toxicity -	Mav cause dr	rowsiness and dizziness.		
single exposure				
Specific target organ toxicity - repeated exposure	Not classified	l.		
Aspiration hazard	May be fatal	if swallowed and enters airways.		
Chronic effects	•	nalation may be harmful.		
		12. Ecological Information		
Ecotoxicity	See below			
Ecotoxicological data Components		Species	Test Results	
Acetone (CAS 67-64-1)				
Crustacea	EC50	Daphnia	13999 mg/L, 48 Hours	
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/L, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/L, 96 hours	
Methyl acetate (CAS 79-20-9)				
Algae	IC50	Algae	120 mg/L, 72 hours	
Crustacea	EC50	Daphnia	1026.7 mg/L, 48 hours	
	EC30	Dapinia	1020.7 mg/L, 40 hours	
Aquatic	1.050		) 005 0 <i>1</i> 0 // 001	
Fish	LC50	Fathead minnow (Pimephales promelas	s) 295 - 348 mg/L, 96 hours	
Naphtha (petroleum), hydrotreate Aquatic	d light (CAS 647	742-49-0)		
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/L, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/L, 96 hours	
			8.8 mg/L, 96 hours	
Persistence and degradability	No data is av	ailable on the degradability of this product		
	NO UALA IS AV	anable of the degradability of this product		
Bioaccumulative potential Mobility in soil	No data avail	able.		
	Not available			
Mobility in general	No other adv			
Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.				
		13. Disposal Considerations		
Disposal instructions		•	iconsod wasto disposal sito. Contonts	
Disposarinstructions	under pressu	eclaim or dispose in sealed containers at l re. Do not puncture, incinerate or crush. I ional/national/international regulations.	Dispose of contents/container in accordance	
Local disposal regulations	•	Dispose in accordance with all applicable regulations.		
Hazardous waste code	-	The waste code should be assigned in discussion between the user, the producer and the waste		
	disposal com	5		

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
	14. Transport Information
Transport of Dangerous Goods (TDG) Proof of Classification	In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue
J.S. Department of Transportation	on (DOT)
Basic shipping requirement	
UN number	UN1950
Proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Hazard class	Limited Quantity - US
Transportation of Dangerous Go	oods (TDG - Canada)
Basic shipping requirement	s:
UN number	UN1950
Proper shipping name	AEROSOLS, flammable
Hazard class	Limited Quantity - Canada
IATA/ICAO (Air)	
Basic shipping requirement	
UN number	UN1950
Proper shipping name	Aerosols, flammable
Hazard class	Limited Quantity - IATA
MDG (Marine Transport)	
Basic shipping requirement	
UN number	UN1950
Proper shipping name Hazard class	AEROSOLS Limited Quantity - IMDG
DOT; IMDG; TDG	Einited Quantity - IMDG
•	15. Regulatory Information
Canadian federal regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.
Canada CEPA Schedule I: L	isted substance
Acetaldehyde (CAS 75-0 Benzene (CAS 71-43-2)	

Naphthalene (CAS 91-20-3)	Listed.		
Canada DSL Challenge Substances: Listed	I substance		
Butane (CAS 106-97-8)	Listed.		
Naphthalene (CAS 91-20-3)	Listed.		
Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number			
Benzene (CAS 71-43-2)	1 TONNES		

Benzene, ethenyl- (CAS 100-42-5) Benzene, ethyl- (CAS 100-41-4) Methanol (CAS 67-56-1) Naphthalene (CAS 91-20-3) Phenol (CAS 108-95-2) Toluene (CAS 108-88-3) Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Acetaldehyde (CAS 75-07-0) Butane (CAS 106-97-8) Propane (CAS 74-98-6) **US state regulations** See below US - California Hazardous Substances (Director's): Listed substance Acetaldehyde (CAS 75-07-0) Listed. Acetone (CAS 67-64-1) Listed. Benzene (CAS 71-43-2) Listed. Benzene, (1-methylethyl)- (CAS 98-82-8) Listed. Benzene, ethenyl- (CAS 100-42-5) Listed. Benzene, ethyl- (CAS 100-41-4) Listed. Butane (CAS 106-97-8) Listed. Cyclohexane (CAS 110-82-7) Listed. Methanol (CAS 67-56-1) Listed. Methyl acetate (CAS 79-20-9) Listed. Naphtha (petroleum), hydrotreated light (CAS Listed. 64742-49-0) Naphthalene (CAS 91-20-3) Listed. Phenol (CAS 108-95-2) Listed. Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (CAS Listed. 128-37-0) Toluene (CAS 108-88-3) Listed. US - Illinois Chemical Safety Act: Listed substance Acetaldehyde (CAS 75-07-0) Acetone (CAS 67-64-1) Benzene (CAS 71-43-2) Benzene, (1-methylethyl)- (CAS 98-82-8) Benzene, ethenyl- (CAS 100-42-5) Benzene, ethyl- (CAS 100-41-4) Butane (CAS 106-97-8) Cyclohexane (CAS 110-82-7) Methanol (CAS 67-56-1) Methyl acetate (CAS 79-20-9) Naphthalene (CAS 91-20-3) Phenol (CAS 108-95-2) Propane (CAS 74-98-6) Toluene (CAS 108-88-3) US - Louisiana Spill Reporting: Listed substance Acetaldehyde (CAS 75-07-0) Listed. Acetone (CAS 67-64-1) Listed. Benzene (CAS 71-43-2) Listed. Benzene, (1-methylethyl)- (CAS 98-82-8) Listed. Benzene, ethenyl- (CAS 100-42-5) Listed. Benzene, ethyl- (CAS 100-41-4) Listed. Butane (CAS 106-97-8) Listed. Cvclohexane (CAS 110-82-7) Listed. Methanol (CAS 67-56-1) Listed. Methyl acetate (CAS 79-20-9) Listed. Naphthalene (CAS 91-20-3) Listed. Phenol (CAS 108-95-2) Listed. Propane (CAS 74-98-6) Listed. Toluene (CAS 108-88-3) Listed. US - Michigan Critical Materials Register: Parameter number Benzene (CAS 71-43-2) BENZENE Benzene, ethenvl- (CAS 100-42-5) STYRENE (MONOMER) Toluene (CAS 108-88-3) TOLUENE US - Minnesota Haz Subs: Listed substance Acetaldehyde (CAS 75-07-0) Listed. Acetone (CAS 67-64-1) Listed. Benzene (CAS 71-43-2) Listed. Benzene, (1-methylethyl)- (CAS 98-82-8) Listed.

Benzene, ethenyl- (CAS 100-42-5)

Listed.

Benzene, ethyl- (CAS 100-41-4) Listed. Butane (CAS 106-97-8) Listed. Cyclohexane (CAS 110-82-7) Listed. Methanol (CAS 67-56-1) Listed. Methyl acetate (CAS 79-20-9) Listed. Naphtha (petroleum), hydrotreated light (CAS Listed. 64742-49-0) Naphthalene (CAS 91-20-3) Listed. Phenol (CAS 108-95-2) Listed. Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (CAS Listed. 128-37-0) Propane (CAS 74-98-6) Listed. Toluene (CAS 108-88-3) Listed. US - New Jersey RTK - Substances: Listed substance Acetaldehyde (CAS 75-07-0) Acetone (CAS 67-64-1) Benzene (CAS 71-43-2) Benzene, (1-methylethyl)- (CAS 98-82-8) Benzene, ethenyl- (CAS 100-42-5) Benzene, ethyl- (CAS 100-41-4) Butane (CAS 106-97-8) Cyclohexane (CAS 110-82-7) Methanol (CAS 67-56-1) Methyl acetate (CAS 79-20-9) Naphtha (petroleum), hydrotreated light (CAS 64742-49-0) Naphthalene (CAS 91-20-3) Phenol (CAS 108-95-2) Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (CAS 128-37-0) Propane (CAS 74-98-6) Toluene (CAS 108-88-3) US - North Carolina Toxic Air Pollutants: Listed substance Acetaldehyde (CAS 75-07-0) Benzene (CAS 71-43-2) Benzene, ethenyl- (CAS 100-42-5) Phenol (CAS 108-95-2) Toluene (CAS 108-88-3) US - Pennsylvania RTK - Hazardous Substances: Special hazard Benzene (CAS 71-43-2) US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant Propane (CAS 74-98-6) US - Texas Effects Screening Levels: Listed substance Acetaldehyde (CAS 75-07-0) Listed. Acetone (CAS 67-64-1) Listed. Benzene (CAS 71-43-2) Listed. Benzene, (1-methylethyl)- (CAS 98-82-8) Listed. Benzene, ethenyl- (CAS 100-42-5) Listed. Benzene, ethyl- (CAS 100-41-4) Listed. Butane (CAS 106-97-8) Listed. Cyclohexane (CAS 110-82-7) Listed. Methanol (CAS 67-56-1) Listed. Methyl acetate (CAS 79-20-9) Listed. Listed. Naphtha (petroleum), hydrotreated light (CAS 64742-49-0) Naphthalene (CAS 91-20-3) Listed. Phenol (CAS 108-95-2) Listed. Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (CAS Listed. 128-37-0) Propane (CAS 74-98-6) Listed. Toluene (CAS 108-88-3) Listed. US - Washington Chemical of High Concern to Children: Listed substance Acetaldehyde (CAS 75-07-0) Benzene (CAS 71-43-2) Benzene, ethenyl- (CAS 100-42-5) Benzene, ethyl- (CAS 100-41-4) Phenol (CAS 108-95-2) Toluene (CAS 108-88-3) **US. Massachusetts RTK - Substance List** Acetaldehyde (CAS 75-07-0) Acetone (CAS 67-64-1)

Benzene, (1-methylethyl)- (CAS 98-82-8) Benzene, ethenyl- (CAS 100-42-5) Benzene, ethyl- (CAS 100-41-4) Butane (CAS 106-97-8) Cyclohexane (CAS 110-82-7) Methanol (CAS 67-56-1) Methyl acetate (CAS 79-20-9) Naphtha (petroleum), hydrotreated light (CAS 64742-49-0) Naphthalene (CAS 91-20-3) Phenol (CAS 108-95-2) Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (CAS 128-37-0) Propane (CAS 74-98-6) Toluene (CAS 108-88-3) US. New Jersey Worker and Community Right-to-Know Act Acetaldehyde (CAS 75-07-0) Benzene (CAS 71-43-2) Benzene, (1-methylethyl)- (CAS 98-82-8) Benzene, ethenyl- (CAS 100-42-5) Benzene, ethyl- (CAS 100-41-4) Butane (CAS 106-97-8) Cyclohexane (CAS 110-82-7) Methanol (CAS 67-56-1) Naphthalene (CAS 91-20-3) Phenol (CAS 108-95-2) Propane (CAS 74-98-6) Toluene (CAS 108-88-3) US. Pennsylvania Worker and Community Right-to-Know Law Acetaldehyde (CAS 75-07-0) Acetone (CAS 67-64-1) Benzene (CAS 71-43-2) Benzene, (1-methylethyl)- (CAS 98-82-8) Benzene, ethenyl- (CAS 100-42-5) Benzene, ethyl- (CAS 100-41-4) Butane (CAS 106-97-8) Cyclohexane (CAS 110-82-7) Methanol (CAS 67-56-1) Methyl acetate (CAS 79-20-9) Naphtha (petroleum), hydrotreated light (CAS 64742-49-0) Naphthalene (CAS 91-20-3) Phenol (CAS 108-95-2) Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (CAS 128-37-0) Propane (CAS 74-98-6) Toluene (CAS 108-88-3) **US. Rhode Island RTK** Acetaldehyde (CAS 75-07-0) Acetone (CAS 67-64-1) Benzene (CAS 71-43-2) Benzene, (1-methylethyl)- (CAS 98-82-8) Benzene, ethenyl- (CAS 100-42-5) Benzene, ethyl- (CAS 100-41-4) Butane (CAS 106-97-8) Cyclohexane (CAS 110-82-7) Methanol (CAS 67-56-1) Naphthalene (CAS 91-20-3) Phenol (CAS 108-95-2) Propane (CAS 74-98-6) Toluene (CAS 108-88-3) **US. California Proposition 65** US - California Proposition 65 - CRT: Listed date/Carcinogenic substance Acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 Benzene (CAS 71-43-2) Listed: February 27, 1987 Benzene, (1-methylethyl)- (CAS 98-82-8) Listed: April 6, 2010 Benzene, ethenyl- (CAS 100-42-5) Listed: April 22, 2016 Listed: June 11, 2004 Benzene, ethyl- (CAS 100-41-4) Naphthalene (CAS 91-20-3) Listed: April 19, 2002 US - California Proposition 65 - CRT: Listed date/Developmental toxin Benzene (CAS 71-43-2) Listed: December 26, 1997

Benzene (CAS 71-43-2)

Country(s) or region	Inventory name		On inve
Inventory status			
Benzene (CAS 71	1-43-2)	Listed: December 26, 1997	
US - California Propo	osition 65 - CRT: Listed date	e/Male reproductive toxin	
Toluene (CAS 10	,	Listed: January 1, 1991	
Methanol (CAS 6	7-56-1)	Listed: March 16, 2012	

Country(s) or region	Inventory name On	inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other Information

LEGEND	HEALTH * 2	
Severe4Serious3Moderate2Slight1Minimal0	FLAMMABILITY 4   PHYSICAL HAZARD 0   PERSONAL X	
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.	
Issue date	02-May-2017	
Version #	01	
Effective date	02-May-2017	
Prepared by	Nu-Calgon Technical Service Phone: (314) 469-7000	
Other information	For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.	