


2-Way Electric Globe Valve Assemblies

Valve Size (inches)		Cv	Close-off Pressure (psi)	Maximum Allowable Diff Pressure (psi)	Actuators - Electric Spring Return 24 Vac				
Stem up, Normally Open					Actuator Description	Manual Override	2-position	Floating	Proportional
2 1/2"	56		125	35	SmartX	Yes	VA-8213-596-5-12	VF-8213-596-5-12	VS-8213-596-5-12
3"	85		125	35	Linear Direct	Yes	VA-8213-596-5-13	VF-8213-596-5-13	VS-8213-596-5-13
4"	145		125	35	Coupled	Yes	VA-8213-596-5-14	VF-8213-596-5-14	VS-8213-596-5-14
5"	240		125	35	 (no separate linkage) 220 lbf min.	Yes	VA-8213-596-5-15	VF-8213-596-5-15	VS-8213-596-5-15
6"	370					Yes	Not available	Not available	Not available
6"	370		125	22	SmartX with linkage 133 lb-in 	Yes	VA-8213-556-5-16	VF-8213-556-5-16	VS-8213-556-5-16
2 1/2"	56		125	35	SmartX	No	VA-8213-576-5-12	VF-8213-576-5-12	VS-8213-576-5-12
3"	85		125	35	with linkage	No	VA-8213-576-5-13	VF-8213-576-5-13	VS-8213-576-5-13
4"	145		125	35	150 lb-in	No	VA-8213-576-5-14	VF-8213-576-5-14	VS-8213-576-5-14
5"	240		125	35	NEMA 4	No	VA-8213-576-5-15	VF-8213-576-5-15	VS-8213-576-5-15
6"	370		125	25		No	VA-8213-576-5-16	VF-8213-576-5-16	VS-8213-576-5-16
Stem up, Normally Closed					Actuator Description	Manual Override	2-position	Floating	Proportional
2 1/2"	56		125	35	SmartX	Yes	VA-8223-596-5-12	VF-8223-596-5-12	VS-8223-596-5-12
3"	85		125	35	Linear Direct	Yes	VA-8223-596-5-13	VF-8223-596-5-13	VS-8223-596-5-13
4"	145		125	35	Coupled	Yes	VA-8223-596-5-14	VF-8223-596-5-14	VS-8223-596-5-14
5"	240		125	35	 (no separate linkage) 220 lbf min.	Yes	VA-8223-596-5-15	VF-8223-596-5-15	VS-8223-596-5-15
6"	370					Yes	Not available	Not available	Not available
6"	370		125	22	SmartX with linkage 133 lb-in 	Yes	VA-8223-556-5-16	VF-8223-556-5-16	VS-8223-556-5-16
2 1/2"	56		125	35	SmartX	No	VA-8223-576-5-12	VF-8223-576-5-12	VS-8223-576-5-12
3"	85		125	35	with linkage	No	VA-8223-576-5-13	VF-8223-576-5-13	VS-8223-576-5-13
4"	145		125	35	150 lb-in	No	VA-8223-576-5-14	VF-8223-576-5-14	VS-8223-576-5-14
5"	240		125	35	NEMA 4	No	VA-8223-576-5-15	VF-8223-576-5-15	VS-8223-576-5-15
6"	370		125	25		No	VA-8223-576-5-16	VF-8223-576-5-16	VS-8223-576-5-16

3-Way Electric Globe Valve Assemblies

Valve Size Cv (inches)		Close-off Pressure (psi)	Maximum Allowable DiffPressure (psi)	Actuators - Electric Spring Return 24 Vac				
Mixing or Diverting				Actuator Description	Manual Override	2-position	Floating	Proportional
2 1/2"	Mix: 85 Divert: A-port: 95 B-port: 115	35	35	SmartX Linear Direct Coupled 	Yes	VA-8303-596-5-12	VF-8303-596-5-12	VS-8303-596-5-12
3"	Mix: 110 Divert: A-port: 110 B-port: 120	35	35		Yes	VA-8303-596-5-13	VF-8303-596-5-13	VS-8303-596-5-13
4"	190	35	35	(no separate linkage) 220 lbf min. 	Yes	VA-8303-596-5-14	VF-8303-596-5-14	VS-8303-596-5-14
5"	290	35	35		Yes	VA-8303-596-5-15	VF-8303-596-5-15	VS-8303-596-5-15
6"	500					Not available	Not available	Not available
6"	500	35	Mix: 15 Divert: 11	SmartX with linkage 133 lb-in 	Yes	VA-8303-556-5-16	VF-8303-556-5-16	VS-8303-556-5-16
2 1/2"	Mix: 85 Diverting: A-port: 95 B-port: 115	35	35	SmartX with linkage 150 lb-in NEMA 4 	No	VA-8303-576-5-12	VF-8303-576-5-12	VS-8303-576-5-12
3"	Mix: 110 Diverting: A-port: 110 B-port: 120	35	35		No	VA-8303-576-5-13	VF-8303-576-5-13	VS-8303-576-5-13
4"	190	35	35		No	VA-8303-576-5-14	VF-8303-576-5-14	VS-8303-576-5-14
5"	290	35	Mix: 35 Divert: 31		No	VA-8303-576-5-15	VF-8303-576-5-15	VS-8303-576-5-15
6"	500	35	Mix: 16 Divert: 12		No	VA-8303-576-5-16	VF-8303-576-5-16	VS-8303-576-5-16

3-Way Electric Globe Valve Assemblies

Valve Size Cv (inches)		Close-off Pressure (psi)	Maximum Allowable DiffPressure (psi)	Actuators - Electric Non-Spring Return 24 Vac			
Mixing or Diverting				Actuator Description	Manual Override	Floating	Proportional
2 1/2"	Mix: 85 Diverting: A-port: 95 B-port: 115	35	35	Forta 337 lbf 	Yes	VU-8303-686-5-12	VU-8303-686-5-12
3"	Mix: 110 Diverting: A-port: 110 B-port: 120	35	35		Yes	VU-8303-686-5-13	VU-8303-686-5-13
4"	190	35	35		Yes	VU-8303-686-5-14	VU-8303-686-5-14
5"	290	35	35		Yes	VU-8303-686-5-15	VU-8303-686-5-15
6"	500	35	35		Yes	VU-8303-686-5-16	VU-8303-686-5-16
6"	500	35	Mix: 32 Divert: 28	SmartX with linkage 300 lb-in 	Yes	VF-8303-516-5-16	VS-8303-516-5-16

3-Way Pneumatic Globe Valve Assemblies

Valve Size Cv (inches)		Close-off Pressure (psi)	Maximum Allowable DiffPressure (psi)	Actuators - Pneumatic Spring Return 24 Vac		
Mixing or Diverting				Actuator Description	Without Positive Positioner	With Positive Positioner
2 1/2"	Mix: 85 Diverting: A-port: 95 B-port: 115	35	35	50 sq. ft. area with linkage 1" nominal stroke 	VK-8303-602-5-12	VK4-8303-602-5-12
3"	Mix: 110 Diverting: A-port: 110 B-port: 120	35	35		VK-8303-602-5-13	VK4-8303-602-5-13
4"	190	35	35		VK-8303-602-5-14	VK4-8303-602-5-14
5"	290	35	35		VK-8303-602-5-15	VK4-8303-602-5-15
6"	370	35	35	50 sq. ft. area with linkage 1-3/4" nominal stroke 	Not available	VK4-8303-652-5-16

2-Way Globe Valve Bodies

Valve Size (inches)	Cv	Part Number	Valve Size (inches)	Cv	Part Number
Stem up, Normally Open			Stem up, Normally Closed		
2 1/2"	56	VB-8213-0-5-12	2 1/2"	56	VB-8223-0-5-12
3"	85	VB-8213-0-5-13	3"	85	VB-8223-0-5-13
4"	145	VB-8213-0-5-14	4"	145	VB-8223-0-5-14
5"	240	VB-8213-0-5-15	5"	240	VB-8223-0-5-15
6"	370	VB-8213-0-5-16	6"	370	VB-8223-0-5-16

3-Way Globe Valve Bodies

Valve Size (inches)	Mixing Cv	Diverting Cv	Part Number
Mixing or Diverting			
2 1/2"	80	A-port: 95 B-port: 115	VB-8303-0-5-12
3"	110	A-port: 110 B-port: 120	VB-8303-0-5-13
4"	190	190	VB-8303-0-5-14
5"	290	290	VB-8303-0-5-15
6"	500	500	VB-8303-0-5-16

Related Literature

F-27193 General Instructions VB-8213 Series 2-1/2" to 6" 125 PSI Flanged Step Up Open Valves

F-27194 General Instructions VB-8223 Series 2-1/2" to 6" 125 PSI Flanged Step Up Closed Valves

F-27197 General Instructions VB-8303 Series 2-1/2" to 6" 125 PSI Flanged Mixing/Diverting Valves

F-27199 Selection Guide VX-8XXX-XXX-S-X Series, VB 8XX3 Series

F-27368-1 Sales Brochure, Flanged Globe Valve with Balanced Plug Technology