

Three Phase ODP Resilient Base Motors

Pumps - Blowers - Conveyors - Industrial Duty

Features:

- Ball Bearing
- Class A and B Insulation
- Continuous Duty
- Open Dripproof
- Single and Two-Speed
- 40°C Ambient
- 60 HZ
- 1/3 thru 5 HP



RB3154A



5BK3202

HP	RPM	Volts	Full Load Amps	Service Factor	Frame	Stock Number	Protector	Insul. Class	Approx. "C"	Dim "AG"	Notes
1-1/2	3450	200-230/460	4.5-4.2/2.1	1.30	56	H531	None	B	11.1	9.1	
		460/200-230	2.3/4.7-4.6	1.30	56H	H843V1	Auto	B	12.9	11.0	26,35,82
		575	1.8	1.15	56H	H944	Auto	B	12.9	11.0	35,82
		575	1.7	1.30	56H	5BK3152	Auto	B	13.7	11.5	1
	1725	200-230/460	5.0-5.0/2.5	1.20	56H	H536	None	B	12.2	10.3	
		208-230/460	5.0/2.5	1.15	56H	RB3154A	Auto	B	11.8	9.8	6,48
		208-230/460	5.0/2.5	1.15	56HZ	RB3154AV1	Auto	B	12.3	10.0	6,15,48
		460/200-230	2.8/5.0-5.6	1.15	56H	H853V1	Auto	B	12.9	11.0	26,35,82
		460/200-230	2.8/5.0-5.6	1.15	145T	H1036	Auto	B	12.8	10.5	
		575	2.0	1.20	56	H943	Auto	B	11.1	9.1	35
		575	2.0	1.20	56H	H960	None	B	12.2	10.3	
	1745/1140	460	2.4/1.2	1.15	56H	H1035	None	B	12.7	8.8	26
		200-230	5.0-4.9/2.9-2.8	1.15	56H	H1034	None	B	12.7	10.8	26
2	3450	200-230/460	6.0-5.5/2.75	1.20	56	H538	None	B	11.4	9.5	
		200-230/460	6.0-5.8/2.9	1.20	56H	BK3202L	Auto	B	13.9	12.1	26
		460/200-230	2.9/6.0-5.8	1.20	56H	H844	Auto	B	13.9	12.0	35,82
		575	2.4	1.20	56H	H952	Auto	B	13.9	12.0	82
	1725	208-230/460	6.8/3.4	1.15	56H	RB3204	None	B	12.8	10.6	
		208-230/460	6.2/3.1	1.15	56H	RB3204A	Auto	B	12.8	10.6	
		208-230/460	6.2/3.1	1.15	56HZ	RB3204AV1	Auto	B	12.8	10.8	
		460/200-230	3.5/6.6-7.0	1.15	56HZ	H854	Auto	B	13.8	11.5	15,35,82
		460/200-230	3.5/6.6-7.0	1.15	145T	H1037	Auto	B	13.8	11.5	
		575	2.4	1.20	56HZ	H1022	Auto	B	13.1	10.8	15
3	3450	460/200-230	4.3/9.0-8.6	1.15	56HZ	H845	Auto	B	13.8	11.5	15,35,82
		460/200-230	4.3/9.0-8.6	1.15	145T	H1038	Auto	B	13.8	11.5	26
		575	3.6	1.15	56HZ	H954	Auto	B	13.8	11.5	15,82
		575	3.5	1.15	56HZ	5BK3302	Auto	B	14.1	11.7	1,15
	1725	460/200-230	4.4/9.0-8.8	1.15	56HZ	H855	Auto	B	14.6	12.3	15,35,82
		575	3.6	1.15	56HZ	H1021	Auto	B	14.6	12.3	1,15
5	3450	208-230/460	13.4-13.2/6.6	1.15	56HZ	H1039L	Auto	B	14.6	12.3	15

Notes:

1. Item to be discontinued when stock is depleted
 6. 50/60 HZ
 15. 56HZ = 7/8" key x 2-5/16" shaft
 26. Extended thru bolts, shaft end only
 35. Quick Connect design bracket
 48. 1.0 Service factor at 50 HZ
 82. Horizontal mount only
- See page 272 for mounting dimensions

Shaft Dimensions

56 = 5/8" Keyed x 1-7/8"
56H = 5/8" Keyed x 1-7/8"

