



# TEMPERATURE/PROCESS INDICATOR

Low Cost, 3-Digit Display, 1% Accuracy



The **Series TID Temperature/Process Indicator** displays temperature or a process value measured by a PTC or NTC thermistor or a 4-20 mA transmitter.

## FEATURES/BENEFITS

- Thermistor or transmitter input models available
- 3 digit bright LED

## APPLICATIONS

- Panel process indication
- Refrigerators, walk in coolers

## SPECIFICATIONS

**Range:** -58 to 302°F (thermistor); -999 to 999 counts (4-20 mA).  
**Input:** PTC/NTC thermistor or 4-20 mA.  
**Power Requirements:** 115 VAC, 230 VAC, 24 VAC/DC.  
**Accuracy:** > 1%.  
**Display:** 3-digits; red, green or blue display.  
**Resolution:** 1° or 0.1 count.  
**Front Panel Rating:** IP64 (NEMA 3R).  
**Weight:** 2.3 oz (65 g).  
**Agency Approvals:** CE, cURus.

## ACCESSORIES

See page reference ❶ below.

MODEL CHART			
Model	Input	Supply Power	Unit
TID-1110	PTC thermistor	115 VAC	°F
TID-1120	PTC thermistor	115 VAC	°C
TID-1410	PTC thermistor	24 VAC/DC	°F
TID-3100	4-20 mA	115 VAC	None
TID-3200	4-20 mA	230 VAC	None
TID-3400	4-20 mA	24 VAC/DC	None