



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	"A" DIM.	FIG.	NOTES
BOHN													
D1124	SP	1/20	115	1500	1	2.1	Open Vent.	CW	SLV	5/16 x 3	3	A	33
D1126	SP	1/15	230	1500	1	1.1	Open Vent.	CW	SLV	5/16 x 3	3 1/2	A	33
D1125	PSC	1/12	208-230	1500	1	0.4	Open Vent.	CCW	SLV	5/16 x 2-5/8	3 3/4	B	20,34
KEEPRITE													
D1120	SP	1/20	115	1500	1	2.1	Open Vent.	CW	SLV	5/16 x 2-1/2	3 1/2	C	
D1121	SP	1/20	208-230	1550	1	1.0	Open Vent.	CW	SLV	5/16 x 2-1/2	3 1/2	C	
D1243	PSC	1/20	115	1550	1	0.8	Open Vent.	CCW	SLV	5/16 x 2-3/4	4 1/8	D	
D1245	PSC	1/20	230	1550	1	0.4	Open Vent.	CCW	SLV	5/16 x 2-3/4	4	D	
KRAMER-TRENTON													
D1152	SP	1/20	115	1500	1	1.7	Open Vent.	CW	SLV	5/16 x 2-3/8	2 7/8	E	
D1154	SP	1/20	230	1500	1	1	Open Vent.	CW	SLV	5/16 x 2-3/8	3 1/8	E	
LARKIN COIL													
D1101	SP	1/20	115	1500	1	1.9	Open Vent.	CCW	SLV	5/16 x 2-1/4	2 3/4	E	33
D1103	SP	1/20	208-230	1500	1	1.15	Open Vent.	CCW	SLV	5/16 x 2-1/4	3	E	33
McQUAY													
D1144	PSC	1/25-1/35-1/65	115	1200	3	1.1-.9-.6	Open Vent.	CW	SLV	3/8 x 5-3/8	4 3/4	F	35
D1142	SP	1/15	115/230	1500	1	1.7-.9	Open Vent.	CW	SLV	5/16 x 2-1/2	3 1/2	G	34
SINGER													
➤ D1164	SP	1/25	115/230	1550	1	1.3-.65	Totally Encl.	CW	SLV	5/16 x 2-1/2	3 1/8	H	
WITT													
D1102	PSC	1/20	115/230	1550	1	.75-.4	Open Vent.	CW	SLV	5/16 x 2-5/8	3 1/2	I	

NOTES: 20: 4M 370V Capacitor included 33: Shell Turbo 68, low temp. oil (-40°F) 34: Bolt Circle = 3.15" 35: PSC use 4M 370V Capacitor



FIG. A D1124, D1126



FIG. B D1125



FIG. C D1120, D1121



FIG. D D1243, D1245



FIG. E D1152, D1154, D1101, D1103



FIG. F D1144



FIG. G D1142



FIG. H D1164



FIG. I D1102