
















# Non-Connected Thermostats

Image	Description	Model	Scheduling	User Interface	Application					Power Method	Sensors			Temperature Setpoint Limits	Display Information		Limited Warranty	Wiring Terminals	Accessories Included			
					Stages	Gas, Oil or Electric	Heat Pump	Milivolt	Linevolt		Wired Outdoor Sensor	Wired Indoor Sensor	Floor/ Slab Sensor		Display Size (Viewable)	On Demand Backlighting						
	T6 Pro	TH6320U2008	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual powered (battery and hardware)	•	•	•	Lockouts only, no display	•		•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, Y2, G, L, K, S and S, O/B, and E and S	UWP mounting system, decorative cover plate, mounting hardware & batteries
		TH6220U2000	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual powered (battery and hardware)	•	•	•	Lockouts only, no display	•		•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, Y2, G, L, K, S and S, O/B, and E and S	UWP mounting system, decorative cover plate, mounting hardware & batteries
		TH6210U2001	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardware)	•	•				•		•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, G, L, O/B, E and K
	T6 Pro Hydronic	TH6100AF2004	7-day, 5-1-1, 5-2, or NP	Soft keys	1 Stage Hot Water Heat Only – No Fan					Dual powered (battery and hardware)	•				•		•	5.44 sq. in.	•	5 Year	R, RC, C, W, S, and S	Floor sensor, UWP mounting system, decorative cover plate, mounting hardware & batteries
	T4 Pro	TH4210U2002	7-day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardware)	•	•			•		•	3.93 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, G, L, O/B, E & K	UWP mounting system, decorative cover plate, mounting hardware & batteries
		TH4110U2005	7-day, 5-1-1, 5-2, or NP	Soft keys	Up to 1 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardware)	•	•			•		•	•	3.93 sq. in.	•	5 Year	R, RC, W, O/B, Y, G, C, L, and K
	TL8100 Hydronic	TL8100A1008	7-Day	Soft keys	Control a line Voltage (120/240VAC) valve or pump or a 24 volt valve	Gas or oil			•	Battery powered	•						•	2.67 sq. in.	•	5 Year	1, 2, 3	Mounting hardware & batteries
	T3 Pro Non-Programmable	TH3210U2004	NP	Soft keys	2 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardware)	•	•			•		•	3.32 sq. in.	•	5 Year	R, RC, C, W, O/B, Y, G, AUX, and E	UWP mounting system, decorative cover plate, mounting hardware & batteries
		TH3110U2008	NP	Soft keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardware)	•	•			•		•	•	3.32 sq. in.	•	5 Year	R, RC, C, W, O/B, Y, and G
	Pro 3000 Non-Programmable	TH3210D1004	NP	Soft keys	2 Heat/1 Cool – Heat Pump only		•			Dual powered (battery and hardware)	•	Manual					•	1.32 sq. in.	•	5 Year	R, C, O, B, Y, G, L, AUX, and E	Mounting hardware & batteries
		TH3110D1008	NP	Soft keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardware)	•	Manual					•	•	1.32 sq. in.	•	5 Year	R, RC, C, O, B, Y, W, and G
	T1 Pro Non-Programmable	TH1110D2009	NP	Soft keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardware)	•	Manual			•		•	2.37 sq. in.	•	5 Year	C, R, RC, W, O/B, Y, G	UWP mounting system, decorative cover plate, mounting hardware & batteries
	E1 PRO Non-Programmable	TH1110E1000	NP	Soft keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardware)	•	Manual					•	3.32 sq. in.	•	2 Year	R, RC, C, W, Y, G, O, and B	Wall-plate, mounting hardware, & batteries
	The Round™	T87K1007	NP	Dial	1 Heat or 1 Cool	•				Power stealing							•	50010944-001	N/A	5 Year	R, W, Y	Mounting hardware
		T87N1000	NP	Dial	1 Heat/1 Cool	•				Power stealing		Manual					•	50010944-001	N/A	5 Year	R, RC, W, Y, G, O, B	Mounting hardware
		T87N1026	NP	Easy-To-See™	1 Heat/1 Cool	•				Power stealing		Manual					•	50010944-001	N/A	5 Year	R, RC, W, Y, G, O, B	Mounting hardware
	Econostat Horizontal	T8034N1007	NP	Slide switches and lever	1 Heat/1 Cool	•				Mechanical		Manual					•	50019661-001	N/A	5 Year	R, RC, W, Y, G, O, B	Mounting hardware
	Econostat	T822K1000	NP	Slide switches and lever	1 Heat	•				Mechanical		Positive off					•	50019661-001	N/A	5 Year	R, W	Mounting hardware
		T827K1009	NP	Slide switches and lever	1 Heat	•		•		Mechanical		Positive off					•	50019661-001	N/A	5 Year	R, W	Mounting hardware
	TL8230	TL8230A1003	7-Day	Soft keys	1 Heat				•	3328 watts @ 208 VAC Max 3840 watts @ 240 VAC Max	•	Positive off					•	2.67 sq. in.	•	5 Year	4-wire DPST	Mounting hardware
	LineVoltPRO™	TL7235A1003	NP	Horizontal lays	1 Heat				•	3600 watts @240 VAC Max 3120 watts @208 VAC Max	•	Positive off					•	2.67 sq. in.	•	3 Year	4-wire DPST	Mounting hardware
	T410A,B Line Voltage Electric Heat	T410A1013 T410A1021 T410B1004	NP	Dial	1 Heat				•	22A @ 120/208/240 VAC Max, 19A @ 277 VAC Max		T410B has positive off			272804A Range Stop and Loading Cover		•	N/A		3 Year	T410A - 2-wire SPST T410B - 4-wire DPST	Mounting hardware
	Line Volt 5-2 Programmable	TH105PLUS	5-2	Buttons	1 Heat				•	3500 watts @240 VAC Max 1700 watts @120 VAC Max	•						•			3 Year	2-wire SPST	Mounting hardware

For more information  
www.resideo.com/pro

**Resideo Technologies, Inc.**  
16100 N 71st Street, Suite 550  
Scottsdale, Arizona 85254  
Office: 480.573.5340  
resideo.com

50-1376 Counterpart | NM | 04/23  
© 2023 Resideo Technologies, Inc. All rights reserved. The Honeywell Home trademark is used under license from Honeywell International, Inc. These products are manufactured by Resideo Technologies, Inc., and its affiliates.

