

DOMESTIC ELECTRIC THERMOSTATS

5441 (CT) DOMESTIC


The 5441 Series is a SPST, slow make and break pilot duty thermostat used on both gas and electric ranges. This control is direct acting (contacts open on temperature rise), and has a mechanical positive "Off" in dial "Off" position. Some models will have an auxiliary switch for "fixed keep warm" and/or "broil" (see ordering chart). Note the electrical rating, as these controls are designed for pilot duty applications only.

5441 Series Uni-Kits have all the features listed above, plus the added convenience of a breakoff dial stem grooved at all standard lengths, plus they include a Slip-Fit®, 4-way dial.


MAXIMUM AMBIENT TEMPERATURE 200°F
UL FILE #E12103

ELECTRICAL RATING

CT1	CT1B	CT2	CT2B	20 VA
CT1E	CT1F	CT2E	CT2F	
CT3	CT3B	21 A @ 240 VAC		
CT5	CT5A	17 A Res @ 120 VAC		
CT7	CT7B	CT8	CT8B	3.6 A Res @ 120 VAC
CT7E	CT7F	CT8E	CT8F	




5441-800
UNI-KIT



- CT1** = For pilot duty. Cross wire contacts to pass very low current.
CT2 = Same as CT1 except have 170°F fixed keep warm switch.
CT3 = Made for electric heaters. Slow make and break contacts.
CT5 = Made exclusively for Corning glass flat top cooking. Have very large contacts for long life.
CT7 = Exclusive for ignitor circuit gas ranges. Make .75 amps at 120V.
CT8 = Same as CT7 except has 170°F fixed keep warm switch.

MOUNTING BRACKET TYPES



ORDERING DATA

CT UNI-KITS

UNI-LINE ORDER NO.	FACTORY MODEL NUMBER	DIAL* TEMP. RANGE °F	CAP. LENGTH	STEM SIZE	STEM LENGTH	STEM FLAT POSITION AT "OFF"	MOUNTING** BRACKET TYPE	BULB O.D. & LENGTH	COMMENTS
5441-100†	CT1E-25-60	140-625	60"	.187	2" KIT	UP	#2	3/16" X 4-3/4"	CT1E REPLACES MOST CT1'S
5441-700†	CT7E-42-66		66"						CT7E REPLACES MOST CT7'S
5441-800†	CT8E-13-60		60"						CT8E REPLACES MOST CT8'S

*Counterclockwise to warmer rotation.

** Mounting bracket adaptor included.

† Four-way dial included.

EXACTS

UNI-LINE ORDER NO.	FACTORY MODEL	TEMP. RANGE °F	CAP. LENGTH	STEM SIZE	STEM LENGTH	STEM FLAT POSITION @OFF	DIAL ROTATION		MOUNTING BRACKET TYPE	BULB O.D. & LENGTH	O.E.M. AND PART NUMBER
							CLOCKWISE TO WARMER	COUNTER-CLOCKWISE TO WARMER			
5441-012	CT1-12-36	140-600	36"	.199	1/2"	UP		•	#3	3/16" x 4-3/4"	GAFFERS & SATTLER 993-443
5441-069	CT7-37-36	150-625	36"		7/8"	LEFT		•		3/16" x 4"	ATHENS STOVE P367-066
5441-071	CT7-1-37	140-600	37"		17/32"	UP		•	#2		ROPER 300087
5441-073	CT7-3-36	150-500 TO BROIL	36"	.187	29/32"	LEFT		•	#1	3/16" X 4-3/4"	CALORIC 70427
5441-077	CT7-7-36				1-27/32"			•			CALORIC 69738
5441-176	CT7-25-36	200-500 TO BROIL		.199	5/8"	DOWN		•			GAFFERS & SATTLER 993-459
5441-177	CT7-22-42	150-550 TO BROIL	42"		3/4"			•	#1		MAGIC CHEF E13LT-31BR