ZR57K3E-TFD

HCFC, R-22, 60Hz, 3- Phase, 460 V

Air Conditioning

Production Status:



Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

45 / 130	45 / 100
65 / 115	65 / 85
58500	68500
5000	3440
7.30	5.60
11.70	19.90
860	880
74 Avg	79 Max
2.0 Avg	3.0 Max
2014-03-06	
	65 / 115 58500 5000 7.30 11.70 860 74 Avg 2.0 Avg

Mechanical

Number of Cylinders:	0	Displ(in^3/Rev):	4.71
Bore Size(in): 0.00 Di		Displ(ft^3/hr):	572.40
Stroke(in):	0.00		
Overall Length (in):	9.69	Mounting Length (in):	7.50
Overall Width (in):	9.69	Mounting Width (in):	7.50
Overall Height (in):	17.24	Mounting Height (in):	17.99 *
Suction Size (in):		7/8 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		62	
Initial Oil Charge (oz)	:	66	
Net Weight (lbs):		85	
Internal Free Volume	(in^3):	257.0	
Horse Power:		4.75	
*Overall compressor mounting grommets.	height on (Copeland Brand Product's	specified

Electrical

LRA-High*:	62.0	MCC (Amps):	12.8	UL File No:	SA-2337				
LRA-Half Winding:		RPM:		UL File Date:	26-Jul-1993				
LRA Low*:		Max Operating Current:	11.0						
RLA(=MCC/1.4;use for contactor se	election):	9.1							
RLA(=MCC/1.56;use for breaker &	wire size	8.2							
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.									

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	<u>Application</u>
R-407C HFC	50	3	380/420	Air Conditioning
R-22 HCFC	50	3	380/420	Air Conditioning
R-407C HFC	60	3	460	Air Conditioning

ZR57K3E-TFD

HCFC, R-22, 60Hz, 3- Phase, 460 V Air Conditioning



Production Status:

Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Service Parts

Reference	Component	Quantity	Description	Comment
99	527-0116-00	1	SPACER-MOUNTING ASSM	
99	529-0060-24	1	POWER CABLE-MOLDED PLU	JG
99	918-0043-00	1	HEATER-CRANKCASE	240V 70W WRAP AROUND
99	918-0043-01	1	HEATER-CRANKCASE	480V 70W WRAP AROUND

ZR57K3E-TFD

HCFC, R-22, 60Hz, 3- Phase, 460 V

Air Conditioning

Production Status:

Copela

Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Accessories

PartNumber	Description
018-0095-00	Crankcase Heater, 240V, 70W, 21" Lead Length
018-0095-01	Crankcase Heater, 480V, 70W, 21" Lead Length
018-0095-02	Crankcase Heater, 575V, 70W, 21" Lead Length
018-0095-03	Crankcase Heater, 240V, 70W, 32" Lead Length
018-0095-04	Crankcase Heater, 240V, 70W, 48" Lead Length
018-0095-05	Crankcase Heater, 480V, 70W, 48" Lead Length
018-0095-06	Crankcase Heater, 575V, 70W, 48" Lead Length
018-0095-07	Crankcase Heater, 120V, 70W, 48" Lead Length
018-0095-08	Crankcase Heater, 400V, 70W, 48" Lead Length
018-0095-09	Crankcase Heater, 277V, 70W, 21" Lead Length
018-0095-00	Crankcase Heater, 240V, 70W, 21" Lead Length
018-0095-01	Crankcase Heater, 480V, 70W, 21" Lead Length
018-0095-02	Crankcase Heater, 575V, 70W, 21" Lead Length
018-0095-03	Crankcase Heater, 240V, 70W, 32" Lead Length
018-0095-04	Crankcase Heater, 240V, 70W, 48" Lead Length
018-0095-05	Crankcase Heater, 480V, 70W, 48" Lead Length
018-0095-06	Crankcase Heater, 575V, 70W, 48" Lead Length
018-0095-07	Crankcase Heater, 120V, 70W, 48" Lead Length
018-0095-08	Crankcase Heater, 400V, 70W, 48" Lead Length
018-0095-09	Crankcase Heater, 277V, 70W, 21" Lead Length
085-0160-00	3 Phase Voltage Monitor. For use with all Copeland 3 Phase Compressors. Consult model family nomenclature for electrical definition in the model number.
527-0116-00	Kit: Spacer Mounting, 30-35 Durometer, 1.45" OD, 0.44" ID, 0.75" Height
918-0043-00	Kit: Crankcase Heater, 240V, 70W, Wrap Around 48" Leads
918-0043-01	Kit: Crankcase Heater, 480V, 70W, Wrap Around 48" Leads
918-0043-02	Kit: Crankcase Heater, 575V, 70W, Wrap Around 48" Leads
918-0043-07	Kit: Crankcase Heater, 120V, 70W, Wrap Around 48" Leads
998-E022-01	Polyol Ester Oil. Approved for use with specific Copeland Hermetic & Semi Hermetic models. Consult specific model family nomenclatures for oil identifier in the model number.

Scott Kohler 05/27/2014

Page 1 of 1



Common U.S. OEM Bill Of Materials

	Suction Connection	Suction Size	Discharge Connection	Discharge Size	Electrical Connection	Mounting Assembly	Sight Glass	Crankcase Heater	Schraeder Valve	Tandem Ready	Module Voltage
230	Stub	7/8"	Stub	1/2"	SCREW 1/2 Conduit	-	-	-	-	-	-
250	Stub	7/8"	Stub	1/2"	SCREW 1/2 Conduit	-	-	-	-	-	-
260	Rotalock	1 1/4"	Rotalock	1"	SCREW 1/2 Conduit	-	-	-	-	-	-
265	Rotalock	1 1/4"	Rotalock	1"	SCREW 1/2 Conduit	-	-	-	-	-	-

Common U.S. Service Bill Of Materials

	Suction Connection	Suction Size	Discharge Connection	Discharge Size	Electrical Connection	Mounting Assembly	Sight Glass	Crankcase Heater	Schraeder Valve	Tandem Ready	Module Voltage
930	Stub	7/8"	Stub	1/2"	SCREW 1/2 Conduit	Yes	-	-	-	-	-
950	Stub	7/8"	Stub	1/2"	SCREW 1/2 Conduit	Yes	-	-	-	-	-
965	Rotalock	1 1/4"	Rotalock	1"	SCREW 1/2 Conduit	Yes	-	-	-	-	-

^{*} Note: For all other Bill Of Material descriptions (Including International and Customer Specific Bills of Materials) contact your sales representative or the Application Engineering Department.